



SLATLEGENDS

TRANSFORM YOUR SPACE *ultra*

All the information is given and based on good building practice and are not a complete statement of all relevant data. Fit & Forget assumes no responsibility for the installation of Slat Legends and their suitability to satisfy relevant Building Codes and Regulations.

Our products are produced with the greatest possible care. However, no guarantee can be given with regards to slight variations in look and colour between different batches.

It is recommended that installations in one room be completed with products bearing the same production date/batch number. Any concerns regarding colour variation or general product appearance must be discussed with Fit & Forget, along with the batch numbers, prior to installation.

Wear protective gear during installation; safety goggles, mask, gloves, ear protection and steel cap boots. Always work in a well ventilated area.

Installation Guide

Prior to installation the panels must be placed on a flat surface for 24hrs in the room where they will be installed, in order to acclimatise with the ambient temperature and humidity of the room.

1. Preparation for installation

The wall you intend to apply the panels to should be smooth, dry and dust free. Check the vertical/horizontal alignment of the wall and mark the necessary guidelines for the first panel placement. Accurately measure the areas around windows, and holes required for electrical sockets, lighting etc and mark the positions on the back of the panels for cutting.

2. Decide on orientation for installation

The panels can be installed vertically or horizontally or diagonally, allowing you to match the visual effect of your interior. You will need to decide which way you are installing before cutting the panels.

3. How to cut Slat Legends Panels

Mark out your required measurements on the back of the panels and cut along the marked line using either a sharp fine tooth hand saw or an electrical jigsaw. Cutting the panels on the back side allows for a cleaner finish on the front. Carefully trim any areas which need to fit around lighting, windows, doors etc.

General Care

- Periodic dusting and vacuuming helps to maintain panel appearance
- Dust with a soft microfiber cloth
- When vacuuming, use a low suction setting and a soft brush attachment
- To avoid discoloration and warping, avoid installing Slat Legends Ultra panels in a location that is subject to prolonged periods of direct sunlight or heat

Spot Cleaning

- Liquids spills should be removed as soon as possible to avoid staining.
- Test any proposed cleaning method on an inconspicuous section before proceeding with a larger area
- Dampen a microfiber cloth using a mild soap and warm water solution.
- Avoid excess pressure or scrubbing as this can cause damage and discoloration
- Remove any excess water by dabbing with a dry soft cloth
- Allow the panel to dry thoroughly with natural airflow.
- Do not use artificial heat (e.g. hairdryer) to dry any areas of the panels.

Tools required

- **Tape measure**
- **Pencil or marker pen**
- **Fine tooth electrical or hand saw**
- **Levelling tool**
- **Silicone/caulking gun**
- **Instant grab adhesive**

4. Adhesive application

The panels should be installed using an instant grab adhesive to ensure an instant strong bond between the wall and the panel. Apply adhesive to the back of the panel in straight strips all down the back, every 5cm. In the case of fitting finishing trims, one strip will suffice.

5. Starting your installation

Panels should be installed from left to right OR from bottom to top (depending on the desired orientation). With the adhesive applied and any levelling adjustments clearly marked, press the first panel into place against the wall. A rubber mallet can be used to tap the panel and further adhere it to the wall. With the first panel secured and level you can now continue the same process for the rest of the required panels. Ensure that each panel is flush up against the previous, and no gaps are showing.

DO NOT USE ABRASIVE OR STEAM CLEANERS



DISCLAIMER: Slat Legends offers these cleaning and maintenance suggestions, however, the customer undertakes cleaning treatment at their own risk. Slat Legends will not be responsible for unsatisfactory results from the proposed treatments contained in this document.

0141 378 7567
sales@ffbg.co.uk
UNIT 8 | BLOCK 8
SPIERSBRIDGE TERRACE
THORNLIEBANK IND ESTATE | G46 8JH



BUILDING & GARDEN PRODUCTS